

DATA SHEET

hallo@tapemonster.de
0761 8879 4575

PP packing tape with digital print · acrylic adhesive, quiet unwind · Version 09/2026 (269)

GENERAL INFORMATION

Available colors	White, brown, transparent
Film type	BOPP (biaxially oriented polypropylene)
Adhesive type	Acrylic, quiet unwind
Printing method	Digital print under the film surface (sandwich print), up to 8 colors or CMYK
Core diameter	76 mm
Application area	Packing tape, quiet unwind, manual application

TECHNICAL DATA

	Typical value	Tolerance / standard
Total thickness	52 µm	EN 1942
Backing thickness	28 µm	–
Adhesive coat weight	24 g/m²	–
Adhesion to steel (180°)	4.5 N/inch ≈ 1.8 N/cm	≥ 3.0 N/inch · EN 1939
Elongation at break	140 %	–
Tensile strength	140 N/mm²	≥ 100 N/mm²
Shear strength	≥ 120 h	EN 1943
Application temperature	from +5 °C	–
Temperature range after application	-10 °C to +60 °C	–

The information above represents average values. Tests and analyses were carried out on randomly selected product samples from ongoing production.

This data is for information purposes only and does not constitute a guarantee for official use. Before making a final selection, we recommend checking whether the article meets your own technical requirements.

The functionality of the product is guaranteed for a period of 6 months from the delivery date.

The product contains **no** hazardous or harmful substances. All our tapes comply with Regulation (EC) No 1907/2006 (REACH).

